

# PROFESSIONAL REFRIGERATION FOR THE PERFECT KITCHEN



*Elanpro's world class equipment has been developed over decades of painstakingly collected market research and customer experience. Our Freezers and Refrigerators come with high quality components from Europe and are known for reliability and performance. They are designed to work under tough Indian conditions. Elanpro machines can be found in Best Hotels, Bars, Restaurants, Pubs, Cafe's and QSR Chains*



CBR-1

- Kitchen Solution • Bar Solution • Confectionery Solution • Ice Machine Solution • Room Solution
- Special Products Solution • Retail Solution • Supermarket Solution

# Salad, Prep & Under Counters - Static & Frost Free Series

## Key Features:

- Stainless steel SS 304
- Dixell digital controller
- HACCP Compliance
- Heavy duty adjustable SS legs / Heavy duty lockable castors
- Environment Friendly Refrigerant
  - R134A for Chillers
  - R404A for Freezers



ES 900



EPS 300



ESH 3000

## Key Features (as applicable):

- EBM Fan Motor
- Removable gasket
- Adjustable shelves
- Lock
- Built in handle



E3F Frost Top



EGN 3V



EVRX 1200 / EVRX 1400

## Optional Features:

- Left or Right side compressor
- Door or drawer options
- Back splash

## Flexi Drawer Undercounter



CBR - 2

### Key Features:

- CFC Free Refrigerant
- User friendly controls with LED Temperature display
- Change drawer temperature from fridge to freezer at the touch of a button
- Auto energy saving hot gas defrost
- Removable gasket for easy cleaning
- GN 1/1 – 150 mm deep pan capacity maximizes available storage space
- Tropicalized to perform at 40°C ambient

## Blast Chiller & Freezers



D-14



D-3

### Key Features:

- CFC refrigerant and foam
- Complete structure interior & exterior in stainless steel with round internal edges for easy cleaning
- Self closing doors with easy to clean and replace magnetic balloon gasket
- Replaceable Electric door mullion heater
- 75mm thickness insulation for excellent thermal efficiency
- Ventilated refrigeration compartment
- Dixell controller and compact footprints
- Danfoss refrigeration components
- EBM Fan

## Premium Series

	Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility	No. of Shelves	Climate Class	Inside/ Outside SS
FROST FREE	ES 900	2 Door Salad Under Counter	240	900 x 700 x 850	-2°C ~ 8°C	2 x GN 1/1 + 3 x GN 1/6	2	32°C	SS 304
	ES 903	3 Door Salad Under Counter	360	1365 x 700 x 850	-2°C ~ 8°C	4 x GN 1/1	3	32°C	SS 304
	EPS 200	2 Door Salad Under Counter with Prep Table	240	900 x 700 x 980	-2°C ~ 8°C	5 x GN 1/6	2	32°C	SS 304
	EPS 300	3 Door Salad Under Counter with Prep Table	360	1365 x 700 x 980	-2°C ~ 8°C	8 x GN 1/6	3	32°C	SS 304
	EVRX 1200	Salad Display Counter	NA	1200 x 335 x 225	-2°C ~ 8°C	5 x GN 1/4	NA	32°C	SS 304
	EVRX 1400	Salad Display Counter	NA	1400 x 335 x 225	-2°C ~ 8°C	6 x GN 1/4	NA	32°C	SS 304
	ESH 2000/800	2 Door Salad Under Counter with Prep Table	337	1510 x 800 x 1050	-2°C ~ 8°C	6 x GN 1/3	2	38°C	SS 304
	ESH 3000/800	3 Door Salad Under Counter with Prep Table	497	2020 x 800 x 1050	-2°C ~ 8°C	10 x GN 1/3	3	38°C	SS 304
	EGN 600 Fish	Reach In Fish Chiller	600	680 x 810 x 2000	-2°C ~ 8°C	NA	5	38°C	SS 304
	E3F	Frost Top	NA	1102 x 678 x 430	-10°C	NA	NA	38°C	SS 304
EGN 3V	Ventilated Cooling Well	NA	1102 x 678 x 533	-2°C ~ 8°C	3 x GN 1/1	NA	32°C	SS 304	

Due to continuous product development, specifications, features and colours are subject to change without notice. Manufactured as per European Technology and Standards. GN pans are optional.

\*Selected models.

## Flexi Drawer Undercounter

Model	Description	Capacity (Ltrs)	Dimension (WxDxH) mm	Temperature Range	GN Compatibility
CBR 1-2	Flexi Drawer Counter	78	905 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	2xGN 1/1
CBR 1-3	Flexi Drawer Counter	116	1230 x 700 x 565	1°C ~ 4°C / -18°C ~ -21°C	3xGN 1/1
CBR 2-2	Flexi Drawer Counter	179	905 x 700 x 830	1°C ~ 4°C / -18°C ~ -21°C	4xGN 1/1
CBR 2-3	Flexi Drawer Counter	262	1230 x 700 x 830	1°C ~ 4°C / -18°C ~ -21°C	6xGN 1/1

Manufactured as per European Technology and Standards

GN Pan are optional

## Blast Chiller & Freezer

Model	Dimension (WxDxH) mm	Capacity (Ltrs)	Cooling Capability*	Tray*	Power Supply	Cooling Mode
D5	800 x 815 x 1015	169	18 kg / 14 kg	5	230 V / 50 Hz	Ventilated
D10	800 x 815 x 1645	368	40 kg / 28 kg	10	230 V / 50 Hz	Ventilated
D14	800 x 815 x 2170	494	55 kg / 38 kg	14	380 V / 50 Hz	Ventilated

Specifications, features and colours are subject to change without any notice, due to continuous product development. \* 70/3°C in 90 minute & 70/-18°C in 240 minute.

**ELANPRO**  
The Commercial Refrigeration Experts

Group  
**thingif(y)**  
Cold Room Cold Chain Monitoring  
@elanprogroup @elanprogroup Elan Professional

Customer Care : +91-88823 02532 ■ Email : care@elanpro.net  
Email : enquiry@elanpro.net ■ Website : www.elanpro.net  
E-Waste Helpline : 1800 258 2550, e-waste@elanpro.net



SCAN TO CONNECT: 8010803166

Authorised Distributor